

# PERFORMANCE & LOADS



FRANCE APPROVED



## FRENCH TECHNICAL APPRAISAL 3034 FROM CSTB

Technical Appraisal n°2.1/15-1673\_V2  
Technical Appraisal n°2.1/18-1791\_V1

## NOTEBOOK 3034 OF CSTB

NF P 01-012:1988  
NF P 01-012:1988

Static load	PRIVATE				PUBLIC				STADIUM (OLD STANDARD)				STADIUM
	0,6 to 1,8kN/ml 700J & 900J				1 to 3kN/ml 700J & 900J				1,7 to 5,1kN/ml 700J & 900J				3 to 9kN/ml 700J & 900J
SABCO	SABCO ORIGINAL				SABCO EVO				SABCO ORIGINAL				SABCO X
GLASS	PROFIL	FLOOR 7010	LATERAL 7011 BUILD-IN-SLAP 7012 LATERAL-OFFSET FIXING 7013	FLOOR 7030	LATERAL 7031	FLOOR 7010	LATERAL 7011 BUILD-IN-SLAP 7012 LATERAL-OFFSET FIXING 7013	FLOOR 7030	LATERAL 7031	FLOOR 7010	LATERAL 7011 BUILD-IN-SLAP 7012 LATERAL-OFFSET FIXING 7013	FLOOR 7019	FLOOR 7019
88/2 PVB Tempered	4W/m 400mm		5W/m 400mm										
88/2 EVA Tempered	4W/m 400mm		5W/m 400mm										
88/2 Trosifol ES Tempered	4W/m 400mm	4W/m 200mm	4W/m 400mm	5W/m 400mm	4W/m 400mm	4W/m 200mm	4W/m 400mm	5W/m 200mm					
88/2 DG41 Tempered	4W/m 400mm	4W/m 200mm	4W/m 400mm	5W/m 400mm	4W/m 400mm	4W/m 200mm	4W/m 400mm	5W/m 200mm					
1010/4 PVB Tempered	4W/m 400mm	4W/m 200mm	4W/m 400mm	5W/m 400mm	5W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 400mm	5W/m 200mm	5W/m 200mm			
1010/2 EVA Tempered	4W/m 400mm	4W/m 200mm	4W/m 400mm	5W/m 400mm	5W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 400mm	5W/m 200mm	5W/m 200mm			
1010/2Trosifol ES Tempered	4W/m 400mm	4W/m 200mm	4W/m 400mm	5W/m 400mm	5W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 400mm	5W/m 200mm	5W/m 200mm	5W/m 200mm	8W/m 150mm	
1010/2 DG41 Tempered	4W/m 400mm	4W/m 200mm	4W/m 400mm	5W/m 400mm	5W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 400mm	5W/m 200mm	5W/m 200mm	5W/m 200mm	8W/m 150mm	
1010/2 Serac 50 Tempered	4W/m 400mm	4W/m 200mm	5W/m 400mm	5W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 500mm	5W/m 200mm	5W/m 200mm	5W/m 200mm	5W/m 200mm	5W/m 200mm	8W/m 150mm
1010/2 Serac 50 No tempered	4W/m 400mm												
1212/2 Serac 60 No tempered	4W/m 400mm	5W/m 200mm	5W/m 400mm										
1212/4 PVB Tempered	4W/m 400mm	4W/m 200mm	4W/m 400mm	5W/m 400mm	5W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 400mm	5W/m 200mm	5W/m 200mm	5W/m 200mm	8W/m 150mm	
1212/2 EVA Tempered	4W/m 400mm	4W/m 200mm	4W/m 400mm	5W/m 400mm	5W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 400mm	5W/m 200mm	5W/m 200mm	5W/m 200mm	8W/m 150mm	
1212/1 SGP Tempered												8W/m 150mm	8W/m 150mm

## LEGEND

<b>SABCO ORIGINAL</b>	<b>SABCO EVO</b>	<b>SABCO x</b>
4W/m 400mm SABCO ORIGINAL Sous Avis Technique	4W/m 400mm SABCO EVO Sous Avis Technique	8W/m 150mm SABCO X Sous Avis Technique
4W/m 400mm SABCO ORIGINAL AT Rated satisfactory	4W/m 400mm SABCO EVO AT Rated satisfactory	8W/m 150mm SABCO X AT Rated satisfactory

4 W/m = 4 Wedges / meter  
400mm = Profile fixing suitable every 400 mm.



# PERFORMANCE & LOADS



**SWITZERLAND APPROVED**



**SWISS STANDARD**  
SIA 261 / SIA 260  
SIGaB

Static load	0,8kN/ml			1,6kN/ml					
Dynamic load	900J			900J					
SABCO	SABCO ORIGINAL			SABCO ORIGINAL					
GLASS	PROFIL	FLOOR 7010	BUILD-IN-SLAP 7012	LATERAL 7011	LATERAL OFFSET FIXING 7013	FLOOR 7010	LATERAL 7011	BUILD-IN-SLAP 7012	LATERAL OFFSET FIXING
1010/2 PVB TVG <i>Heat-strengthened</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm						
1010/2 EVA TVG <i>Heat-strengthened</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm						
1010/2 DG41 TVG <i>Heat-strengthened</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm						
1010/2 Trosifol ES TVG <i>Heat-strengthened</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm						
1010/2 SGP TVG <i>Heat-strengthened</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm						
1010/2 PVB ESG <i>Tempered</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm
1010/2 EVA ESG <i>Tempered</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm
1010/2 DG41 ESG <i>Tempered</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm
1010/2 Trosifol ES ESG <i>Tempered</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm
1010/2 SGP ESG <i>Tempered</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm
1212/2 PVB TVG <i>Heat-strengthened</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm						
1212/2 EVA TVG <i>Heat-strengthened</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm						
1212/2 DG41 TVG <i>Heat-strengthened</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm						
1212/2 Trosifol ES TVG <i>Heat-strengthened</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm						
1212/2 SGP TVG <i>Heat-strengthened</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm						
1212/2 PVB ESG <i>Trempé thermique</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm
1212/2 EVA ESG <i>Tempered</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm
1212/2 DG41 ESG <i>Tempered</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm
1212/2 Trosifol ES ESG <i>Tempered</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm
1212/2 SGP ESG <i>Tempered</i>	4W/m 400mm	4W/m 200mm	4W/m 400mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm	4W/m 200mm

## LEGEND

**SABCO ORIGINAL**

4W/m  
400mm SABCO ORIGINAL  
Under Swiss Standard

4W/m  
400mm SABCO ORIGINAL  
Swiss standard Rated satisfactory

4 W/m = 4 Wedges / meter  
400mm = Profile fixing suitable every 400 mm.

# PERFORMANCE & LOADS



BELGIUM APPROVED



**BELGIUM STANDARD**  
NBN B03-004

Static load	PRIVATE			PUBLIC			STADIUM
	0,5kN/ml - 1kN			1kN/ml - 1kN			Royal decree KB3kN/ml + 20%
Dynamic load	150J			225J - 350J			150J - 225J - 350J
SABCO	SABCO ORIGINAL			SABCO EVO	SABCO ORIGINAL		
GLASS	PROFIL	FLOOR 7010	LATERAL 7011 BUILD-IN-SLAP 7012	FLOOR 7030	FLOOR 7010	LATERAL 7011 BUILD-IN-SLAP 7012	FLOOR 7010
	66/2 DG41 <i>Heat-strengthened</i>			4W/m 400 mm Wind class 0			
88/2 DG41 <i>Heat-strengthened</i>	4W/m 400 mm Wind class 0		4W/m 400 mm Wind class 2				
1010/2 DG41 <i>Float</i>	4W/m 400 mm Wind class 2		4W/m 400 mm Wind class 2	4W/m 400 mm Wind class 2			
1010/2 DG41 <i>Heat-strengthened</i>	4W/m 400 mm Wind class 7	4W/m 400 mm Wind class 6	4W/m 400 mm Wind class 2	4W/m 400 mm Wind class 7	4W/m 400 mm Wind class 6	4W/m 200 mm	
1212/2 DG41 <i>Heat-strengthened</i>	4W/m 400 mm Wind class 7	4W/m 400 mm Wind class 6	4W/m 400 mm Wind class 2	4W/m 400 mm Wind class 7	4W/m 400 mm Wind class 6	4W/m 200 mm	

Reference speed	vb,0 (m/s)	Wind exposure class 1				Wind exposure class 2				Wind exposure class 3			
		26	25	24	23	26	25	24	23	26	25	24	23
Roughness categories land		Reference heights up (ze)				Reference heights up (ze)				Reference heights up (ze)			
Coastal area	0												
Countryside	I									2m	2m	4m	5m
Rugged landscape	II			2m	3m	3m	3m	4m	6m	5m	6m	8m	11m
Industrial area - forest	III	5m	6m	7m	9m	9m	12m	15m	19m	15m	19m	5m	21m
City	IV	15m	17m	21m	25m	25m	30m	30m	30m	30m	30m	30m	30m
Max.dynamic pressure	qp(ze)=	544 Pa				693 Pa				815 Pa			

Reference speed	vb,0 (m/s)	Wind exposure class 4				Wind exposure class 5				Wind exposure class 6			
		26	25	24	23	26	25	24	23	26	25	24	23
Roughness categories land		Reference heights up (ze)				Reference heights up (ze)				Reference heights up (ze)			
Coastal area	0	3m				5m				8m			
Countryside	I	4m	5m	8m	11m	7m	10m	14m	22m	12m	14m	27m	42m
Rugged landscape	II	8m	11m	15m	16m	14m	16m	16m	22m	16m	16m	27m	42m
Industrial area - forest	III	21m	21m	21m	21m	21m	21m	21m	22m	21m	21m	27m	42m
City	IV	30m	30m	30m	30m	30m	30m	30m	30m	30m	30m	30m	42m
Max.dynamic pressure	qp(ze)=	950 Pa				1086 Pa				1224 Pa			

Reference speed	vb,0 (m/s)	Wind exposure class 7			
		26	25	24	23
Roughness categories land		Reference heights up (ze)			
Coastal area	0	15m			
Countryside	I	21m	31m	48m	78m
Rugged landscape	II	21m	31m	48m	78m
Industrial area - forest	III	21m	31m	48m	78m
City	IV	30m	31m	48m	78m
Max.dynamic pressure	qp(ze)=	1364 Pa			

## LEGEND

SABCO ORIGINAL

4W/m SABCO ORIGINAL  
400mm Under Belgium standard

4W/m SABCO ORIGINAL  
400mm Belgique standard Rated satisfactory

4 W/m = 4 Wedges / meter  
400mm = Profile fixing suitable every 400 mm.

SABCO EVO

4W/m SABCO EVO  
400mm Under Belgium standard

4W/m SABCO EVO  
400mm British standard Rated satisfactory

# PERFORMANCE & LOADS



UNITED KINGDOM APPROVED



BRITISH STANDARD  
BS EN 6180:2011

Static load	0,36 kN/ml						0,74 kN/ml				1,5 kN/ml				3 kN/ml			
	SABCO ORIGINAL			SABCO EVO			SABCO ORIGINAL		SABCO EVO		SABCO ORIGINAL		SABCO EVO		SABCO X			
GLASS	PROFIL	FLOOR 7010	LATERAL 7011 BUILD-IN-SLAP 7012	LATERAL-OFFSET FIXING 7013	FLOOR 7030	LATERAL 7031	SOL 7010	LATERAL 7011 BUILD-IN-SLAP 7012	LATERAL-OFFSET FIXING 7013	SOL 7030	LATERAL 7031	FLOOR 7010	LATERAL 7011 BUILD-IN-SLAP 7012	LATERAL-OFFSET FIXING 7013	FLOOR 7030	LATERAL 7031	FLOOR 7019	FLOOR 7019
	15mm Monolithic	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm							
88/2 PVB Tempered	4W/m 400mm	4W/m 400mm	4W/m 400mm															
88/2 EVA Tempered	4W/m 400mm	4W/m 400mm	4W/m 400mm															
88/2 Trosifol ES Trepé	4W/m 400mm	4W/m 400mm	4W/m 400mm			4W/m 400mm	4W/m 400mm	4W/m 400mm										
88/2 DG41 Tempered	4W/m 400mm	4W/m 400mm	4W/m 400mm			4W/m 400mm	4W/m 400mm	4W/m 400mm										
88/2 SGP Tempered	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm		4W/m 400mm	4W/m 400mm								
19mm Monolithic	4W/m 400mm	4W/m 400mm	4W/m 400mm			4W/m 400mm	4W/m 400mm				4W/m 400mm							
1010/4 PVB Tempered	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm								
1010/4 EVA Tempered	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm							
1010/2 Trosifol ES Tempered	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm							
1010/2 DG41 Tempered	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm					
1010/2 SGP Tempered	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm	4W/m 400mm					
1212/2 SGP Tempered	4W/m 400mm			4W/m 200mm	4W/m 200mm	4W/m 200mm			4W/m 400mm	4W/m 400mm	4W/m 200mm			4W/m 200mm	4W/m 200mm			
1212/1 SGP Tempered			8W/m 400mm double fixing					8W/m 400mm double fixing					8W/m 400mm double fixing			8W/m 200mm	8W/m 200mm	

## LEGEND

SABCO ORIGINAL

4W/m  
400mm SABCO ORIGINAL  
Under British Standard

4W/m  
400mm SABCO ORIGINAL  
BS Rated satisfactory

SABCO EVO

4W/m  
400mm SABCO EVO  
Under British Standard

4W/m  
400mm SABCO EVO  
BS Rated satisfactory

SABCO x

8W/m  
200mm SABCO X  
Under British Standard

4 W/m = 4 Wedges / meter  
400mm = Profile fixing suitable every 400 mm.

# PERFORMANCE & LOADS



ITALY APPROVED



ITALY STANDARD  
UNI 11678:2017

Static load	1 to 1,5kN/ml		2 to 3kN/ml		3 to 4,5kN/ml		
Dynamic load	350J (Height 700mm)		350J (Height 700mm)		600J (Height 1200mm)		
SABCO	SABCO ORIGINAL		SABCO ORIGINAL		SABCO ORIGINAL		
GLASS	PROFIL	FLOOR 7010	LATERAL 7011	FLOOR 7010	LATERAL 7011	FLOOR 7010	LATERAL 7011
1010/4 EVA Tempered		5W/m 200 mm	5W/m 200 mm	5W/m 200 mm			
1010/4 DG41 Tempered		5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	
1010/4 Trosifol ES Tempered		5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	
1010/2 SGP Tempered		5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	
1212/4 EVA Tempered		5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	
1212/4 DG41 Tempered		5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm
1212/4 Trosifol ES Tempered		5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm
1212/2 SGP Tempered		5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm	5W/m 200 mm

## LEGEND

SABCO ORIGINAL

5W/m  
200mm SABCO ORIGINAL  
Under Italy standard

5W/m  
200mm SABCO ORIGINAL  
Italy standard Rated satisfactory

5 W/m = 5 Wedges / meter  
200mm = Profile fixing suitable every 200 mm.

# PERFORMANCE & LOADS



GERMAN APPROVED



ABP Nr 16-057P  
German regulation DIN  
18008-4

Static load	PRIVATE			PUBLIC			
	0,5kN/ml			1kN/ml			
Dynamic load	900J			900J			
SABCO	SABCO ORIGINAL			SABCO ORIGINAL			
GLASS	PROFIL	FLOOR 7010 BUILD-IN-SLAP 7012	LATERAL 7011	LATERAL OFFSET FIXING 7013	FLOOR 7010	LATERAL 7011 BUILD-IN-SLAP 7012	LATERAL OFFSET FIXING 7013
	1010/2 PVB TVG <i>Heat-strengthened</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm
1010/2 EVA TVG <i>Heat-strengthened</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1010/2 DG41 TVG <i>Heat-strengthened</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1010/2 Trosifol ES TVG <i>Heat-strengthened</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1010/2 SGP TVG <i>Heat-strengthened</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1010/2 PVB ESG <i>Tempered</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1010/2 EVA ESG <i>Tempered</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1010/2 DG41 ESG <i>Tempered</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1010/2 Trosifol ES ESG <i>Tempered</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1010/2 SGP ESG <i>Tempered</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1212/2 PVB TVG <i>Heat-strengthened</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1212/2 EVA TVG <i>Heat-strengthened</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1212/2 DG41 TVG <i>Heat-strengthened</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1212/2 Trosifol ES TVG <i>Heat-strengthened</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1212/2 SGP TVG <i>Heat-strengthened</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1212/2 PVB ESG <i>Tempered</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1212/2 EVA ESG <i>Tempered</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1212/2 DG41 ESG <i>Tempered</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1212/2 Trosifol ES ESG <i>Tempered</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	
1212/2 SGP ESG <i>Tempered</i>	4W/m 400 mm	4W/m 200 mm	4W/m 400 mm	4W/m 200 mm	4W/m 200 mm	4W/m 200 mm	

## LEGEND

SABCO ORIGINAL

4W/m  
400mm SABCO ORIGINAL  
Under ABP

4W/m  
400mm SABCO ORIGINAL  
ABP Rated satisfactory

4 W/m = 4 Wedges / meter  
400mm = Profile fixing suitable every 400 mm.